

#09-R-2208875 109-911295
1419886

SKID STEER WITH BUCKET AND COLD PLANNER TO MEET
THE FOLLOWING SPECIFICATIONS

This unit shall come with high-flow hydraulics which gives the unit the capacity to run various attachments to its maximum capacity and shall also have joy stick controls.

ENGINE:

Five (5) cylinder minimum
Gross horsepower: 76 minimum
Net horsepower: 70 minimum
Aspiration: Turbocharged
Air Cleaner: Dry element
Fuel: Diesel

ELECTICAL SYSTEM

12 Volt

TRANSMISSION/STEERING

Type: Hydrostatic-Servo
Travel Speed: Two speed low 0-6 mph minimum
Two speed high 0-11 mph maximum

AXLES/TIRES/BRAKES

Axle: One-piece forged shafts; no-maintenance oil bath lubrication of inner and outer axle bearings
Brakes: Spring applied, hydraulically released wet-disk park brake
Tires: 12X16.5 brawler solid flex

HYDRAULIC SYSTEM

Total pump flow with high-flow: 34 GPM minimum
High flow: 63 horsepower minimum

LOADER PERFORMANCE

Tipping Load: 5000 lb. minimum
Bucket breakout with heavy duty construction bucket: 5,300 lb minimum
SAE rated operating capacity: 2500 lbs minimum

DIMENSIONS

Length without bucket: 115.5 in. minimum
Length with bucket: 138.5 in. minimum
Width without bucket: 73.7 in. minimum
Height to ROPS: 80.9"
Dump height: 100 in. minimum
Dump reach with heavy-duty construction bucket: 41 in minimum
Ground clearance: 9 in. minimum

PS, 1 OF 2

109-911295

1419886

Front turn radius: 83.7 in. maximum
Dump angle (at full lift height) 45 degrees
THIS UNIT SHALL COME WITH THE FOLLOWING OPTIONAL
FEATURES

Block heater
Transmission: 2 speed low
High-flow hydraulics
Backup alarm
Dual flashers
Handle Kit 8 button
Horn
Warning beacon Kit
Hand controls
Rear weight brackets
Bucket: 78" heavy duty construction

THIS SKID STEER MUST COME WITH A 1 YEAR FACTORY
WARRENTY PLUS A 4 YEAR ADDITIOINAL POWER
TRAIN/HYDRAULIC WARRENTY

COLD PLANER

This unit shall have fingertip, electrical control of tilt, depth, and side shift for positioning. This unit shall also have hinged access cover and have a one-year warranty.

Specifications:

Hydraulic flow rate: 29-41 gpm
Hydraulic pressure: 2,500-3500 psi
Hydraulic horsepower: 42-72 hp
Planing width: 24 in.
Planing depth: 0-5 in.
Tilt capability: Plus or minus 8 degrees
Side-shift capability: -3-22 in.
Number of carbide teeth: 57
Operating weight: 2,400 lb.

MFR: John Deere
Model: 325 or equal