

QUANTITY: One
 YEAR OF MFG: New
 CAPACITY: 8,000 lbs @ 24" Load Center
 ENGINE: 6 Cylinder Diesel, 80- Horsepower ~~MINIMUM~~
 FUEL: Diesel
 TRANSMISSION: Dual-Speed Automatic
 DIRECTION CONTROL: Lever on Column
 STEERING: Hydrostatic Power Steering, Tilt Steering Column
 SEAT: Full-Suspension Vinyl with Operator Restraints, Operator Present System includes interrupt, auto-mast lock, return-to-neutral

 BRAKES: Standard Drum Brakes, Hydraulic Boosted Brakes
 AIR INTAKE: Standard High Air Intake with Pre-Cleaner
 TIRES: Front Dual-Drive Tires -Solid, Rear Single Solid
 MAST TYPE: 2 Stage, 145" Lift, 97" Lowered Height
 MAST TILT: Standard, - 6 Degree/6 Degree
 FORK SIZE: 48" Long, Hook Type
 CARRIAGE SIZE: Approximately 48" Wide, ITA Class III
 CARRIAGE TYPE: Hook Style, 47" SS-Fork Positioner
 LOAD BACKREST: 48" High and width of carriage
 OPERATOR COMP: Standard Overhead Guard w/Cover
 HYDRAULICS: 3-Way, state location of levers (seat-side, cowl, etc)
 LIGHTS: Two Headlights, One Rear Work light, Brake & Backlight Lights

 FUEL CAPACITY: 26 to 30 gallons
 MANUALS: Operator's Manual, Parts Manual, Maintenance Manual

 WARRANTY: 12 Months or 2,000 hours, plus 24/4,000 power train warranty

 SAFETY EQUIPMENT: Amber Strobe Light (low mount), Audible Reverse Alarm, Horn, Neutral Start Switch, Large Size Rearview Mirror, Fire Extinguisher.

 Hour Meter, Engine coolant temperature gauge and fuel gauge

All other items required by OSHA or ANSI

Price Should Include Delivery to Alabama Department of Transportation, Mobile, Alabama, 1701 West I65 Service Road North.

Must have a Service/Parts Facility within 50 miles of Alabama Department of Transportation Mobile, Alabama, 1701 West I65 Service Road North.