

SKID STEER WITH BUCKET AND COLD PLANNER TO MEET  
THE FOLLOWING SPECIFICATIONS

This unit shall come with high-flow hydraulics which gives the unit the capacity to run various attachments to its maximum capacity and shall also have joy stick controls.

ENGINE:

Gross horsepower: 75 minimum  
Aspiration: Turbocharged  
Air Cleaner: Dry element  
Fuel: Diesel

ELECTICAL SYSTEM

12 Volt

TRANSMISSION/STEERING

Type: Hydrostatic-Servo  
Travel Speed: Two speed low 0-6 mph minimum  
Two speed high 0-11 mph maximum

AXLES/TIRES/BRAKES

Axle: Oil bath lubrication of inner and outer axle bearings (permanent sealed)  
Brakes: Spring applied, hydraulically released wet-disk park brake  
Tires: 12X16.5 brawler solid flex or equal

HYDRAULIC SYSTEM

Total pump flow with high-flow: 34 GPM minimum

LOADER PERFORMANCE

Tipping Load: 5000 lb. minimum  
Bucket breakout with heavy duty construction bucket: 5,300 lb minimum  
SAE rated operating capacity: 2500 lbs minimum

DIMENSIONS

Dump height: 100 in. minimum  
Dump reach with heavy-duty construction bucket: 32.5 in minimum  
Ground clearance: 8" in. minimum  
Dump angle (at full lift height) 41 degrees minimum

THIS UNIT SHALL COME WITH THE FOLLOWING OPTIONAL  
FEATURES

Four season cab with heater, defroster and air conditioner

Block heater  
Transmission: 2 speed low  
High-flow hydraulics  
Backup alarm  
Dual flashers  
Handle Kit 8 button  
Horn  
Warning beacon Kit  
Hand controls  
Rear weight brackets  
Bucket: 74" minimum heavy duty construction

THIS SKID STEER MUST COME WITH A 1 YEAR FACTORY  
WARRENTY PLUS A 4 YEAR ADDITIOINAL POWER  
TRAIN/HYDRAULIC WARRENTY

COLD PLANER

This unit shall have fingertip, electrical control of tilt, depth, and side shift for positioning. This unit shall also have hinged access cover and have a one-year warranty.

Specifications:

Hydraulic flow rate: 29-40 gpm  
Hydraulic pressure: 2,500-3500 psi  
Hydraulic horsepower: 42-72 hp  
Planing width: 24 in.  
Planing depth: 0-5 in.  
Tilt capability: Plus or minus 8 degrees  
Side-shift capability: -3-22 in.  
Number of carbide teeth: 57 minimum  
Operating weight: 2,400 lb.

MFR: John Deere  
Model: 325 or equal

Other Sources:  
Thompson Tractor  
Loader Services

Trigreen Equipment