

- 1 Ea. New current year model or latest year end production model Crawler Tractor (Low Ground Pressure) with power angle, power tilt inside mounted blade; meeting the following specifications in accordance with manufacturer's standard published specifications.

Engine: Diesel; 96 net flywheel horsepower; 24 or 12 volt electric system; 60 amp alternator.

Transmission: Type: Hydrostatic drive.

Steering: Wet disc, oil bath type, or hydraulically controlled (with single lever control).

Service Brakes: Shall be oil bath. Parking brake to be provided.

Undercarriage: Track gauge to be at least 65", grousers to be a minimum 25" and maximum 28" wide low ground pressure. Six (6) bottom rollers per side and life-time lubricated. Tractor shall have sealed and lubricated track chains and hydraulic track adjusters. Ground clearance 13" or more. Must have at least 91" of track on ground. Full rock guards.

Blade: Power Angle and Tilt, at least 120" wide and at least 35" in height with a raise height of at least 30" and tilt 16" to either side with float position. A blade angle of 22 degrees minimum.

Ripper: 3 Shanks minimum.

Operating Weight: At least 19,750 lbs.

Root Rake: Front Mount

Other Equipment: ROPS cab w/heater & defroster; air conditioners (not roof mounted); work lights; back-up alarm; track guiding guards, full length; drawbar; engine side panels; front pull hook; radiator sand screen or severe service radiator; engine and transmission guard; armchair type suspension seat with seat belt; vandalism protection with locks; instrument gauges to monitor all critical functions; cold weather starting aid.

Warranty: 5 year/3,000 hours full machine warranty to include oil analysis (no deductible).

Vendor to furnish two (2) sets of parts books, service manuals, technical manuals and operators' manuals with unit when delivered.

Delivery date may be a factor in making award. Must furnish three (3) sets of keys.