

#10-R-2220651

**SPECIFICATIONS
FORKLIFT - 9,000 LB, DIESEL POWERED**

Reqn # : 309 - 030658
SNAP # : 1443813

Bids requested for one (1) 9,000lb capacity, diesel-powered forklift, new, latest model of current year manufacture, to meet or exceed the following specifications:

- CAPACITY: 9,000lb @ 24" Load Center
- ENGINE : Minimum 4-cylinder diesel, minimum 80hp @ 2400rpm
- FUEL: Low-sulfur Diesel
- TRANSMISSION: Dual-speed automatic, 2 forward, 1 reverse
- DIRECTION CONTROL: Lever on steering column or foot pedal
- STEERING: Hydrostatic power steering, tilt column
- SEAT: Full-suspension vinyl with operator restraint, with Operator Present System including interrupt, auto mast lock, return-to-neutral
- BRAKES: Standard drum or disc brakes, hydraulic boost
- AIR INTAKE: Standard high air intake with pre-filter
- TIRES: Tires to be pneumatic or pneumatic shaped solid
Dual front drive tires, single rear
- MAST TYPE: Two-stage, minimum 143" lift, maximum 100.5" overall lowered height
- MAST TILT: Standard, minimum 5° forward / rearward
- FORK SIZE: 60" Long, hook-type
- CARRIAGE SIZE: Approx. 48" wide, ITA Class III
- CARRIAGE TYPE: Hook-style, 47" Side-shift fork positioned
- LOAD BACKREST: 48" high, width of carriage
- OPERATOR COMPARTMENT: Overhead roll-over guard with enclosed cab and heater
- HYDRAULIC CONTROL: 4-way
- LIGHTS: Two(2) headlights, one(1) rear work light, tail lights, brake lights, backup light
- FUEL CAPACITY: Minimum 20 gallons
- MANUALS: Operator's, Parts, Service
- WARRANTY: 12 months / 2,000 hours plus 24mo/4,000hr power train warranty
- SAFETY EQUIPMENT: Amber strobe light, low mount; Audible reverse alarm, horn, neutral start switch, large rearview mirror, fire extinguisher
- INDICATORS: Hour meter, Engine coolant temperature gauge, fuel gauge

Must include all features and components required by OSHA or ANSI.

Bid price shall include delivery F.O.B. to ALDOT loading dock, prepped and ready to operate. Dealer must have a Service/Parts facility within 50 miles of delivery location.