

909-390857/1511497

13-R-2253221

FORKLIFT SPECIFICATIONS

QUANTITY:	One
BRAND/MODEL	Hyster - H80FT or Equal
YEAR OF MFG:	2013 Year Model <i>OR NEWER</i>
CAPACITY:	8,000 lbs @ 24" Load Center
ENGINE:	Tier 3 or 4 Diesel, 74 Horsepower or Greater
TRANSMISSION:	Two-Speed Autoshift, Rear Drive Handle w/Horn Button on OHG Leg
TRANS/INCH CONTROLS:	Column Fwd/Rev Lever; Dual Inch/Brake Pedals
STEERING:	Hydrostatic Power Steering, Tilt Steering Column
SEAT:	Full-Suspension Vinyl with Operator Restraints, Operator Present System, and Seat Belt
BRAKES:	Internal Oil Cooled Wet Disc Brakes
AIR INTAKE:	Standard High Air Intake with Pre-Cleaner
TIRES:	Dual-Drive, Solid Pneumatic, Single Steer
MAST TYPE:	2 Stage, Minimum 143" Lift, Lower Height Not to Exceed 98"
MAST TILT:	6 Degree Forward / 12 Degree Back
FORK SIZE:	2" Thick x 5" Wide x 48" Long, Standard Taper
CARRIAGE SIZE:	Standard ITA Class III, Maximum 60" Wide
ATTACHMENT:	Sideshift/Fork Positioner, Maximum 62" Wide
LOAD BACKREST:	Standard 48" High, and width of carriage
OPERATOR COMP:	Standard Overhead Guard w/Plexiglas Top Cover
HYDRAULICS:	4-Way, Valve/Hoses, 4 Lever Manual Controls
LIGHTS:	Headlights, Rear Work light, Brake/Tail/Backup
FUEL CAPACITY:	Minimum 20 gallons
MANUALS:	Operator's Manual, Parts Manual, Maintenance
WARRANTY:	12 Months/2,000 Hours Standard Comprehensive, 36 Months/6,000 Hours Powertrain Warranty
SAFETY EQUIPMENT:	Amber Strobe Light (low mount), Audible Reverse Alarm, Horn, Neutral Start Switch, Rear View Mirrors, Fire Extinguisher, All Standard Gauges All other items required by OSHA or ANSI

Pg. 1 OF 1